

EVO15 Gold

Passive 2-ways Point Source Array Speaker

The EVO15 Gold are high performance passive 2-way loudspeakers. Employing a single 15" driver in a bass-reflex enclosure of installed sound applications. Designs using a 1.4" exit driver and large horns for accurate pattern control. They provide rotatable dispersion characteristics of 60° x 75° . With a frequency response extending from 40Hz to 20kHz (processed), the cabinets can be used as full range systems or supplemented by different subwoofers of the VS-series.



Specifications

Acoustics	EVO15 Gold
Power handling capacity/peak	1400W(Program)/2800W(peak 10ms)
Frequency response	40~20kHz(processed)
Maximum SPL	132dB(processed)*
Nominal impedance	4 Ω
Coverage	60°×75°(15°+ 60°) HF-horn, rotatable
LF driver	1x 15" cone driver
Voice coil	4"
HF driver	1×1.4" exit with 3" diaphragm ferrite transducers

Remark: * Peak level at 1m under half space conditions using pink noise with crest factor 4.

Connector

2x NEUTRIK® NL4 SPEAKON parallel INPUT/OUTPUT: +1/-1; LINK: +2/-2

Cabinet

CNC made 15mm birch plywood; Handling: 2 handles;
Front: coated steel grille; Finish: black polyurea spot spray.

Weight/Size

N.W/G.W	40kg/51kg
Product Dimensions	W446xH746xD500mm
Package Dimensions	W613xH562xD870mm

