



The P10 is a high performance passive 2-way loudspeaker.

A single 10" ferrite driver in the bass reflex cabinet and different high frequency sections is suitable for sound applications in a variety of installations.

They offer 90° x 70° rotatable dispersion characteristics.

With a frequency response extending from 55Hz to 18kHz (processed), these cabinets can be used as a full-range system or complemented by different subwoofers from the SUB or VS series.

**Description:**

2-way full range Loudspeaker

**Power handling capacity / peak:**

700W(program) / 1400W(peak)

**Frequency response:**

55~18kHz (processed)

**Maximum SPL:**130dB \*

**Nominal impedance:**8Ω

**Coverage:**

90° x 70° HF-horn, rotatable

**Transducers:**

LF:1×10" cone driver V.C:3"

HF:1×1" exit with 1.75" diaphragm

**Acoustical load:**bass-reflex

**Connect:**

2xNEUTRIK® NL4 SPEAKON® parallel

**Input/Output:**+1/-1;Link:+2/-2

**Cabinet:**

15mm birch plywood made by CNC

**Front:**steel grill with coating

acoustically neutral 3D fabric

**Finish:**black polyurea spot spray

**Product DIM (mm):**

W309xH580xD370

**Net Weight:**

21.2kg / 46.7lb

*\*Peak level at 1 m under half space conditions using pink noise with crest factor 4*

