

CLUB212

PREMIUM EUROPEAN CUSTOM MADE DRIVERS

CRYSTALLINE SOUND

IMPRESSIVE DESIGN FOR IMPRESSIVE CLUBS

ALL COLORS ON DEMAND

电子两分频高声压顶级酒吧全频音箱

世界上最高品质的欧洲钹铁单元

怪兽级电音重放极品

不凡的设计只属于不凡的你



AT A GLANCE

Real 1300W RMS power capacity (8 hours pink noise)

Natural sound and incredible holographic reproduction

Optimized for smooth frequency response in and out axis

Premium custom made European drivers

Proprietary 50/90° x 0/70° asymmetric horn

Heavy braced birch plywood cabinet

All colors and finish available on demand

APPLICATIONS

It 's all in its name, the CLUB 212 is specifically designed and engineered to meet the requirements of the most high end and prestigious clubs and night live locations. It 's astonishing design will be a perfect addition to your location. That 's why Verity Audio offers the CLUB 212 with all kinds of colors and finishes. The CLUB 212 is also engineered with club music in mind, and will be able to deliver an enormous SPL and wide dynamic over a well controlled surface due to its unique asymmetrical horn design.

The CLUB 212 speaker is best matched with a Verity Audio SUB range subwoofer.

SPECIFICATIONS

Power Capacity / Puissance admissible (50~15000Hz pink noise 8 hours)	1300W RMS / 2600W program
Nominal impedance / Impédance nominale	4Ω
Frequency response / Réponse en fréquence (-6dB half space, no EQ)	52~19000Hz
Manufacturing Consistency tolerance / Tolérance de fabrication	±1.5dB from 300 to 10000Hz
Average Sensitivity / Sensibilité moyenne	102dB/W/m (wideband 200~16000Hz)
Calculated Maximum Pressure / Pression acoustique maximale (SPL / 1m)	134dB continuous / 137dB Program
Nominal Directivity / Directivité nominale (-6dB)	Asymmetric horn 50° H UP en 90° H Down & 70° V Down above 1000Hz
Recommended low cut filter / Coupe bas conseillé	70~120Hz with subwoofer
Low Frequency driver / Haut parleur de grave	Custom made European 12" driver, Neodymium magnet, 3" voice coil
High Frequency driver / Haut parleur d'aigu	Custom made European 1.4" exit driver, Neodymium magnet, 3" voice coil, ti diaphragm
Crossover / Filtre acoustique	No, external DSP processor required. (recommended cut 1400Hz, 12 dB/oct on LF, 24dB/oct on HF)
Flying hardware / Équipement d'accroche	6 holes for shakles
Connectors / Connectique	1x NEUTRIK Speakon® NL4MP (1+/1- Input for LF, 2+/2- Input for HF)
Floor Monitor use / Usage retour de scène	No
Pole mount / Support pour pieds	Omnimount type 75
Cabinet / Caisse	CNC made with tongue and groove assembly 15mm birch plywood
Finish / Finition	Touring grade textured black mat coating
Size / Taille (WxHxD)	700x588x698mm
Weight / Poids	32kg net, 40kg gross

VIEW

