

V4.25

COMPACT, LIGHT WEIGHT AND HIGH POWER IN 2U
SUITABLE FOR ALL V-AUDIO SPEAKERS RANGE
PART OF THE ALL-IN-ON V-RACK



AT A GLANCE

High power amplifier 4x 2100W 4Ω (V4.25) continuous

4 input / 4 output configuration

High efficiency exclusive Class I topology

Designed to match all the Verity Audio speakers

Equipped exclusively with high-end components

Best used on a 32A single phase 220V supply

APPLICATIONS

The V4.series is specially designed for Verity Audio. The high power it delivers can drive any Verity Audio speaker flawlessly. It's lightweight and compact, meeting the actual industry standard requirements.

The V4.series amplifiers are part of the V-Rack, a complete ready to go package. Loved by the professional rental companies due to its reliability and all-in one compact setup.

SPECIFICATIONS

Power	V4.25
8 Ω *	1300W x4
4 Ω *	2100W x4
2 Ω **	2500W x4
8 Ω bridge*	4200W x2
4 Ω bridge**	5000W x2
Other Specification	
Frequency response	20Hz~20kHz (+0 / -1.5dB)
THD+N	<0.05%
S/N rate	>80dB
Damping factor	>800 (100Hz)
Crosstalk	>65dB
Slew rate	>10v/ μ s
Input sensitivity	26dB / 32dB / 38dB / 0.775v / 1v / 1.4v
Input impedance	20k Ω / 10k Ω
Voltage gain (8 Ω)	42.3dB
Output circuitry	Class I
Cooling	Air flow from front to rear
Connector	
Input	NEUTRIK ®XLR-F
Output	NEUTRIK ® <i>Speakon NL4</i>
Function	
Front pane indicato	On / SIG / Limit / VU / Protect indicator
Front panel	Power switch / Volume control
Rear panel	Operation mode
Dimension/weight	
Product dimensions(mm)	483x412x89
Packing dimensions(mm)	595x565x170
G.W.	15.6kg
Power	AC 110v~240v / 60Hz, 50Hz, \pm 10%

VIEW



Rear Panel

Remark:

- 1、*,The power is tested under the condition of 40ms burst, 1KHz sine wave and 1% THD.
- 2、**,The power is tested under the condition of 20ms burst, 1KHz sine wave and 1% THD.
- 3、 The final specification is subject to the user manual.