



COL4.3

EUROPEAN NEODYMIUM DRIVER
VERY IMPRESSIVE SOUND QUALITY
VERY ACCURATE VERTICAL DIRECTIVITY
CRYSTALLINE SOUND THAT WILL BLOW YOUR SENSES
MATCH PERFECTLY WITH SUB210S
TO EXTEND THE LOW FREQUENCY RANGE TO 38Hz
4x3"定制单元
170Hz-13500Hz接近完美全频段响应
大声压级，过载能力强
丰富的泛音，真实自然的声音
紧凑的体积，灵活的组合与吊挂

AT A GLANCE

High accurate vertical directivity.
Premium european custom made drivers
MDF cabinet
High quality gloss-free white painting

APPLICATIONS

Thanks to his design, finishing and clear sound. COL4.3 loudspeaker system is suitable for new trending places such bars and luxury entertainment spaces as:

- High-end Bar and Disco
- Luxury KTV
- Commercial Audio
- Cinema
- Home Theater
- Small Mobile Performance

Recommend Subwoofer: SUB210S

SPECIFICATIONS

Drivers	4x3" Full Range European Neodymium driver
Power Capacity	120W AES 240W Program, 480W Peak
Nominal impedance	8Ω
Frequency response	170Hz-13.5kHz (-6dB)
Sensitivity	99dB 1W/1m half space
Maximum SPL(calculated)	120dB Continuous, 123dB Program, 126dB Peak
Horizontal directivity(-6dB)	120° ±30° 800Hz-5kHz, 60° ±10° 6kHz-16kHz
Vertical directivity(-6dB)	20° ±5° 2.5kHz-8kHz, 40° ±25° 1kHz-13.5kHz
Recommended low cut filter	Butterworth 12dB/oct 160Hz
Connectors	1x Euroblock (Phoenix connector) 42A rated with locking screws
Cabinet	CNC made 12mm MDF, smooth non glossy white painting
Finish	Satin painted
Dimensions(WxHxD)	W114xH400xD119mm
Mounting	Flying: 2 M6 insertion points on top and rear for eye bolts Wall: 4 M5 insertion points on rear face for swivel-tilting wall/pole bracket 2 M6 insertion points on top and bottom for "U" bracket Pole: 2 M4 insertion points on bottom face for pole adaptor
Weight	3kg

VIEW

