



COL8.3

EUROPEAN NEODYMIUM DRIVER
VERY IMPRESSIVE SOUND QUALITY
VERY ACCURATE VERTICAL DIRECTIVITY
CRYSTALLINE SOUND THAT WILL BLOW YOUR SENSES
MATCH PERFECTLY WITH SUB210S
TO EXTEND THE LOW FREQUENCY RANCE TO 38Hz

8x3"定制单元
180Hz-16000Hz接近完美全频段响应
大声压级，过载能力强
丰富的泛音，真实自然的声音
紧凑的体积，灵活的组合与吊挂

AT A GLANCE

High accurate vertical directivity.
Premium european custom made drivers
MDF cabinet
High quality gloss-free white painting

APPLICATIONS

Thanks to his design,finishing and clear sound. COL8.3 loudspeaker system is suitable for new trending places such bars and luxury entertainment spaces as:

- High-end Bar and Disco
- Luxury KTV
- Commercial Audio
- Cinema
- Home Theater
- Small Mobile Performance

Recommend Subwoofer:SUB210S

SPECIFICATIONS

Drivers	8x3" Full Range European Neodymium driver
Power Capacity	240W AES 480W Program, 960W Peak
Nominal impedance	4Ω
Frequency response(-6dB)	180Hz-16kHz Switch 10°, 180Hz-13kHz Switch 20°
Sensitivity	101dB 1W/1m
Maximum SPL(calculated)	125dB Continuous, 128dB Program, 131dB Peak
Horizontal directivity(-6dB)	120° ± 30° 800Hz-5kHz, 50° ± 15° 6kHz-16kHz
Vertical directivity(-6dB)	Switch 10°: 10° ± 5° 2kHz-16kHz Switch 20°: 20° ± 5° 1.3kHz-16kHz
Recommended low cut filter	Butterworth 12dB/oct 160Hz
Connectors	Euroblock (phoenix connector) 42A rated with locking screws
Cabinet	12mm MDF
Finish	Satin painted
Dimensions(WxHxD)	114x720x110mm
Mounting	Flying: 2 M6 insertion points on top and rear Wall: 4 insertion points on rear for wall bracket Pole: 2 insertion points on bottom for pole support
Weight	5kg

VIEW

