



COL16.3

EUROPEAN NEODYMIUM DRIVER
VERY IMPRESSIVE SOUND QUALITY
VERY ACCURATE VERTICAL DIRECTIVITY
CRYSTALLINE SOUND THAT WILL BLOW YOUR SENSES

16x3"定制单元
180Hz-14000Hz接近完美全频段响应
大声压级，过载能力强
丰富的泛音，真实自然的声音
紧凑的体积，灵活的组合与吊挂

AT A GLANCE

High accurate directivity.
Premium european custom made drivers
Heavy braced HDF cabinet
High quality gloss-free white painting

APPLICATIONS

The COL16.3 loudspeaker system is suitable for new trending places such as bars and luxury entertainment spaces such as:

- Medium size Mobile Performance
- High-end Bar and Disco
- Luxury KTV
- Commercial Audio
- Cinema
- Home Theater

SPECIFICATIONS

Drivers	16x3" Full Range European Neodymium driver
Power Capacity	480W AES 960W Program, 1920W Peak
Nominal impedance	4Ω
Frequency response / Réponse en fréquence	180Hz-13kHz Switch 20°, 180Hz-14kHz Switch 30°
Sensitivity	104dB 1W/1m
Maximum SPL(calculated)	131dB Continuous, 134dB Program, 137dB Peak
Horizontal directivity(-6dB)	120°±30° 800Hz-5kHz, 50°±15° 6kHz-16kHz
Vertical directivity(-6dB)	Switch 20°: 20°±5° 700Hz-8kHz Switch 30°: 30°±5° 400Hz-9kHz
Connectors	Euroblock(phoenix connector) 42A rated with locking screws
Cabinet	12mm MDF
Finish	Satin painted
Dimensions(WxHxD)	114X1400X119mm
Mounting	Flying: 2 M6 insertion points on top and rear for eye bolts Wall: 4 M5 insertion points on rear face for swivel-tilting wall / pole 2 M6 insertion points on top and bottom for "U" bracket Pole: 2 M6 insertion points on bottom face for pole adaptor
Weight	10.6kg

VIEW

