
## Puissant 10 ———





Description:

2-way full range Loudspeaker **Power handling capacity / peak:** 700W(program) /1400W(peak)

Frequency response: 55~18kHz (processed) Maximum SPL:130dB \* Nominal impedance:8Ω

Coverage:

90° x 70° HF-horn, rotatable

Transducers:

LF:1×10" cone driver V.C:3" HF:1×1" exit with 1.75" diaphragm Acoustical load:bass-reflex

\*Peak level at 1 m under half space conditions using pink noise with crest factor 4

The Puissant10 is a high performance passive 2-way loudspeaker.

A single 10" ferrite driver in the bass reflex cabinet and different high frequency sections is suitable for sound applications in a variety of installations.

They offer 90° x 70° rotatable dispersion characteristics.

With a frequency response extending from 55Hz to 18kHz (processed), these cabinets can be used as a full-range system or complemented by different subwoofers from the SUB or VS series.

## Connect:

2xNEUTRIK® NL4 SPEAKON® parallel Input/Output:+1/-1;Link:+2/-2

Cabinet:

15mm birch plywood made by CNC **Front**:steel grill with coating

acoustically neutral 3D fabric

Finish: Rain cover UV protection

Product DIM (mm): W309xH580xD370

Net Weight:

21.2kg / 46.7lb

